

909-990942

1417544

2208920

Specification For Portable Light Towers

- ENGINE:** Tier 2 Diesel engine 10.5 to 13.5 HP @ 1800 to 2000 RPM, 12 volt electrical system, water cooled, fuel tank capacity 25 to 34 gallons with fuel gauge, fuel water separator, spin-on oil and fuel filters, dry type air filter, automatic high engine coolant temperature and low engine oil pressure shut-down.
- GENERATOR:** Output 6 kw to 10 kw at 1800 to 2000 RPM, frequency – HZ 60, available receptacles (1) 120V, 15A GFCI Duplex; (1) 240 V, 30A.
- LIGHT HEAD:** Four light 1,000 watt metal halide lamps, aluminum reflector housings and tempered impact-resistant glass lenses, weather-resistant, twist-lock connections for attaching floodlights, lights should be manually adjustable.
- TOWER:** Telescoping mast, with 360-degree rotation and position lock, extends from 12' to 30', mast retracts and stows horizontally for travel, able to stand up to 65 mph wind speed with outriggers extended and jacks down, locking system to prevent telescoping during travel.
- TRAILER:** Four point jack/outrigger, highway ready, combination hitch with 3" pintle eye and 2" ball hitch with safety chains, all running lights-stop/turn/clearance, 13" tires, four tie-downs
- Warranty:** Minimum one year for the package.